



LAWRENCE
LIVERMORE
NATIONAL
LABORATORY

LLNL-TR-661081

GeGI (Germanium Gamma Imager) Performance: Maritime Interdiction Operation

J. G. Dreyer, M. T. Burks, D. Trombino

September 23, 2014

Disclaimer

This document was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor Lawrence Livermore National Security, LLC, nor any of their employees makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or Lawrence Livermore National Security, LLC. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or Lawrence Livermore National Security, LLC, and shall not be used for advertising or product endorsement purposes.

This work performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344.

GeGI (Germanium Gamma Imager) Performance: Maritime Interdiction Operation

Contact: Jonathan Dreyer, 925-424-3160, dreyer4@llnl.gov
Morgan Burks, 925-423-2798, burks5@llnl.gov
Dave Trombino, 925-423-0430, trombino1@llnl.gov

Exercise: Maritime Interdiction Operation

Date: August 13-14, 2014

Location: Point Alameda, Alameda California

Summary of Results

The Gamma Ray Imager (GeGI) was demonstrated during the Maritime Interdiction Operation at Point Alameda, the site of the former Naval Air Station, in Alameda, CA. During this exercise GeGI was used to localize sources within an abandoned building and a cargo ship, the Admiral Callaghan. Key points from this exercise include:

- Demonstrated portable, high-resolution gamma-ray imager
- Demonstrated viability of gamma-ray imaging for interdiction scenarios
- Operated in field environment w/out power for full work day
- Localized various radioactive sources throughout a cargo ship and in buildings

Summary of System Performance

GeGI is a portable gamma-ray imager weighing less than 30lbs. It was easily transported between the various measurement locations by car and could be hand carried onto the cargo vessel. With the hot-swappable external batteries (each weighing 1.8lbs) the instrument was operated throughout the day without the need of AC power.



Figure 1 The Germanium Gamma-Ray Imager (GeGI) with attached PC for instrument control and data storage. The 180° panoramic camera provides an optical photograph to overlap on the Compton and Pinhole images.

This work was performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344.
LLNL-TR-661081

Measurement 1: Source Localization within a Building

GeGI was fielded for two days at an abandoned building in Point Alameda. The configuration of GeGI with laptop and batteries is shown in Figure 2. A ^{137}Cs and ^{60}Co source were placed in within a room of the building and GeGI was used to locate the sources. On the first day the ^{137}Cs was localized from within the room (see Figure 3) and from an adjacent room (Figure 4), for each case the time to localize the source required less than 10 seconds and 5.6 minutes, respectively. On the second day additional measurements (shown in Figure 6) were conducted with both ^{60}Co and ^{137}Cs . In all cases GeGI successfully localized the sources of radiation.



Figure 2 GeGI setup in a room of the abandoned building. GeGI was successfully able to localize sources within the room and from an adjacent room.




Figure 3 Compton image localizing a ^{137}Cs source placed in the ceiling. With GeGI located in the same room the source was localized within 10 seconds.



Figure 4 A Compton image of the same ^{137}Cs source shown in Figure 3, located in an adjacent room. The additional attenuation of the walls increased the time to localization from 10 seconds (GeGI within the room), to 5.6 minutes.




Figure 5 The spectrum taken for 15mins of the ^{60}Co and ^{137}Cs sources shown in Figure 6.




Figure 6 The Compton image of the ^{60}Co and ^{137}Cs sources located within the ceiling and a desk, respectively.

Measurement 2: Source Localization within a Cargo Ship, Admiral Callaghan

GeGI was also used to locate sources within a cargo ship, the Admiral Callaghan. A ^{60}Co , ^{137}Cs , and uranium source were placed in several storage bins and on the floor. GeGI located the ^{60}Co and ^{137}Cs source within 138 and 80 seconds, respectively. The uranium source was located using the 610 keV gamma ray within 60 seconds.



Figure 7 GeGI was used to localize three sources within the Admiral Callaghan cargo ship. The uranium source is located in the blue container, center. The ^{60}Co and ^{137}Cs source were placed in storage bins approximately 30ft from the detector.




Figure 8 The spectrum taken for 35mins of the ^{60}Co , ^{137}Cs and uranium source shown in Figure 7. The ^{214}Bi , ^{226}Ra , and ^{214}Pb are decay products of the ^{238}U decay chain.




Figure 9 Compton image of the three sources taken within the cargo ship.